



City of North Port
Neighborhood Development Services
4970 City Hall Boulevard
North Port, Fl. 34286

Phone (941) 429-7044 Fax (941) 429-7180 Email: bldginfo@cityofnorthport.com Inspections (855) 941-4636

SUBMITTAL CHECKLIST FOR AN ABOVE GROUND POOL PERMIT

Please Submit the following Information and this Checklist with the Application for Construction

1. ___ Building Permit Application
2. ___ 3 copies of survey indicating the location of the pool with 3 setbacks (2 sides and 1 rear). * Also indicate the location of the Electrical Service, Equipment and all Concrete Pads for Equipment. (if required for operation of pool)
3. ___ Pools 24" to 47" above ground require a 48" barrier (fence). Design of the fence is described in the Florida Building Code Section 424.2.17. Fences surrounding the pool area that have gates are required to be self closing and self latching with a mechanism to open the gate a minimum of 54" above the ground to meet the requirements of the Pool Safety Act per FBC Section 424.2.17.1.8. All windows and doors opening into the enclosed pool area are required to be alarmed to meet the requirements of the Pool Safety Act per FBC 424.2.17.1.9
4. ___ Pools 48" or higher above ground require a removable ladder or other means to meet the barrier requirements of the Pool Safety Act per FBC 424.2.17.1.10 thru 424.2.17.1.15
5. ___ Will the installation of this above ground pool require ANY Electrical Work.?
6. ___ 3 Copies of the Pool Safety Act

*Above ground pools shall not be located within 10 horizontal feet from any overhead service drop conductors less than 22 ½ feet above the ground.

Communication cables crossing over and above pool shall not be less than 10 feet above the pool.

Underground wiring shall not be within 5 feet of the inside wall of the pool unless the wiring is necessary to supply the pool equipment.

Extension cords are not permitted for connection of pool equipment. Receptacle outlets must be located within reach of the factory installed cords on all equipment. All wiring to pool equipment must be suitable for the purpose and be of approved materials. Receptacle outlets shall be weather-resistant and tamper-resistant type and incorporate a weatherproof cover listed for use in a wet location as specified in section 406.8 and 406.11 of the NEC. Factory installed cords from the pool equipment shall not pass through any window, doors, or fixed enclosure. Cords from the pool equipment shall not be buried.